



## GIUNTO TRE PEZZI FEMMINA-FEMMINA

ANSI B16.11

3000 - 6000 LBS

## FEMALE-FEMALE UNIONS

ANSI B16.11

3000 - 6000 LBS

Diam. nominale ND	3000				6000			
	Q <sup>(1)</sup>		R <sup>(1)</sup>		Q <sup>(1)</sup>		R <sup>(1)</sup>	
	mm	inches	mm	inches	mm	inches	mm	inches
1/4"	42.5	1.67	36.0	1.42	54.0	2.13	46.0	1.81
3/8"	47.5	1.87	41.0	1.62	57.0	2.25	51.0	2.00
1/2"	52.0	2.05	46.0	1.81	69.0	2.72	60.0	2.36
3/4"	57.0	2.25	56.0	2.20	72.0	2.84	72.0	2.84
1"	63.0	2.48	65.0	2.56	80.0	3.15	80.0	3.15
1 1/4"	68.0	2.76	80.0	3.07	89.0	3.50	94.0	3.70
1 1/2"	78.0	3.07	88.0	3.39	108.0	4.25	100.0	3.94
2"	91.0	3.50	105.0	4.06	114.0	4.49	122.0	4.80
2 1/2"	120.0	4.49	122.0	4.80	130.0	5.13	144.0	5.67
3"	140.0	5.12	144.0	5.67	150.0	5.91	180.0	7.09
4"	148.0	5.91	200.0	7.09				

<sup>(1)</sup> Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.  
*Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.*