



MANICOTTI RIDOTTI S.W.

ANSI B 16.11
3000 - 6000 LBS

REDUCING COUPLINGS S.W.

ANSI B 16.11
3000 - 6000 LBS

Diam. nominale Nominal pipe size	3000				6000			
	Q ⁽¹⁾		R ⁽¹⁾		Q ⁽¹⁾		R ⁽¹⁾	
	mm	inches	mm	inches	mm	inches	mm	inches
3/8" x 1/4"	25.4	1	24.9	0.98	25.4	1	26.7	1.05
1/2" x 3/8"	28.7	1.13	31.0	1.22	28.7	1.13	33.0	1.30
1/2" x 1/4"	28.7	1.13	31.0	1.22	28.7	1.13	33.0	1.30
3/4" x 1/2"	35.0	1.38	36.0	1.42	35.0	1.38	40.1	1.58
3/4" x 1/4"	35.0	1.38	36.0	1.42	35.0	1.38	40.1	1.58
1" x 3/4"	38.1	1.50	45.2	1.78	38.1	1.50	50.0	1.97
1" x 1/2"	38.1	1.50	45.2	1.78	38.1	1.50	50.0	1.97
1" x 1/4"	38.1	1.50	45.2	1.78	38.1	1.50	50.0	1.97
1 1/4" x 1"	38.1	1.50	55.1	2.17	38.1	1.50	57.9	2.28
1 1/2" x 1"	38.1	1.50	60.0	2.36	38.1	1.50	65.0	2.56
1 1/2" x 3/4"	38.1	1.50	60.0	2.36	38.1	1.50	65.0	2.56
1 1/2" x 1/2"	38.1	1.50	60.0	2.36	38.1	1.50	65.0	2.56
2" x 1/2"	51.3	2.02	74.9	2.95	51.3	2.02	82.0	3.23
2" x 1"	51.3	2.02	74.9	2.95	51.3	2.02	82.0	3.23

⁽¹⁾ Le dimensioni non elencate nell'ANSI B 16.11-1980 e BS 3799-1974 possono variare a seconda del produttore.
Dimensions not listed in ANSI B 16.11-1980 and BS 3799-1974 may vary according to the manufacturer.